

INSECO, Inc.

TECHNICAL DATA SHEET

560 Series

PAVER SEAL Rx

“Wet Look Finish”

Enhancer & Sealer

BioBased

Inseco 560 Paver Seal is a water based alternative to Inseco 660 Clear Seal. It is an environmentally friendly, protective finish designed to seal and enhance the color of concrete pavers. 560 Paver Seal penetrates into the surface and produces a tough, durable, clear film that will enhance the pavers color similar to its solvent based counterparts, 560 Paver Seal binds the joint sand and protects against water damage, staining and UV ray damage. 560 Paver Seal also provides mildew protection and tremendous resistance against wear from both foot and vehicular traffic. 560 Paver Seal may be applied to damp pavers which allows for same day cleaning and sealing.

RECOMMENDED USES:

For properly prepared concrete and brick pavers, slate, Saltillo tiles and clay roof tiles.

SURFACE PREPARATION:

Dirt, grease, grime and any foreign material must be removed before application of new coating. Treat surface for mildew. Oil and grease should be scrubbed with a solution of TSP and water. Contact an Inseco representative for detailed surface preparation specifications.

Do not apply to painted surfaces.

APPLICATION INFORMATION:

Mix product thoroughly and apply with brush, roller or airless sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 50 Deg. F. Do not apply if the threat of rain exists or if moisture or dew may condense on the surface prior to 560 Paver Seal curing. Cover and protect all vegetation and surrounding areas not being sealed. Do not over apply, soak the substrate or allow product to puddle. Two thin coats are recommended for best performance.

RECOMMENDED THINNER:

560 Paver Seal does not require thinning and should be used as is, directly from the container.

TECHNICAL DATA:

Finish: Sheen

Pigment Type: None

Vehicle Type: Bio Based Polymer

Solvent Type: Water

% Solids By Weight: 37% +/- 2%

% Solids By Volume: 33% +/- 2%

Density: 8.45 lbs. per gallon

Viscosity @ 75 deg. F (24 deg. C): Waterlike

Coating VOC: <50 g/l

Flash Point, Minimum: Not Flammable

Flame Spread: Class A rating on non-combustible substratum

Estimated Dry Time:

Touch - 30-60 minutes

Recoat - 2 hours

Foot Traffic - 24 Hours

Vehicular Traffic - 72 Hours

Clean Up: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 300-400 square feet per gallon.

560 Paver Seal is water based. Do not Freeze.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. A Povia Paints representative should be contacted with any questions concerning product information or application procedures. Our products conform to Povia quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.